

CLEARLY NET™ SYSTEM IS A SUPERIOR OPTION COMPARED TO OTHER SKIMMERS

FEATURES	NET™ SYSTEM	OTHER FABRIC SYSTEMS	SOLID BELT SYSTEM	PNEUMATIC SYSTEMS
LPH ADSORPTION CAPACITY	High	High	Low	N/A
APPLICATION IN FLUCTUATING WATER TABLE CONDITIONS	Unlimited Range	Unlimited Range	Unlimited Range	2 to 3 feet
VARIABLE RECOVERY RATE	Yes	Yes	No	No
ADAPT TO VARYING BELT WIDTHS	Yes	Yes	No	N/A
HOUSING DURABILITY	Stainless Steel	Stainless Steel	Painted Carbon	Stainless Steel
REQUIRE ANCILLARY EQUIPMENT (air hoses, compressor, etc.)	No	No	No	Yes
BELOW GRADE INSTALLATION	Yes	No	Yes	Yes
INTEGRATE WITH GW DEPRESSION PUMPS (dual-extraction)	Yes	Yes	Yes	Yes
INTEGRATE WITH VACUUM EXTRACTION PROCESSES	Yes	No	Yes	Yes
TOTALLY ENCLOSED HOUSING (closed loop)	Yes	No	Yes	N/A
OIL SEEPS FROM HOUSING	No	Yes	Yes	N/A
APPLICATION IN 2-INCH WELLS	Yes	No	Yes	Yes
FIELD AJUSTMENT OF BELT FABRIC	Yes	Yes	No	N/A
THERMAL AND GFCI OPTIONS	Standard	Not Standard	Not Standard	N/A
RECOVER PRODUCTS-LIGHT FRACTION TO DISTILLATES	Yes	Yes	Moderate	Moderate
GAUGING PROVISION DURING EQUIPMENT OPERATION	Yes	No	No	No
EASY WELL HEAD MOUNTING	Yes	No	No	N/A
EMERGENCY OVERFLOW PROTECTION	Yes	No	No	N/A
OPERATE ON SOLAR AS A SOLE POWER SOURCE	Yes	Yes	Yes	No
EXPLOSION-PROOF MOTOR OPTION AVAILABLE	Yes	No	Yes (only option)	N/A
USED IN RECOVERY/RECHARGE TESTS	Yes	No	No	No
BIOFOULING/ENCRUSTATION	No	No	No	Yes
LIGHT-WEIGHT AND EASY TO INSTALL	Yes	No	No	No
OPERATION AND MAINTENANCE COST	Low	Medium	High	High
VAPOR TIGHT SEAL OPTION	Yes	No	Yes	Yes

N/A - Not Applicable